Republic of the Philippines
City of Cagayan de Oro
BIDS AND AWARDS COMMITTEE

cagayan de Oro
city of golden friendship

REQUEST FOR QUOTATION
(Negotiated 53.1 of the 2016 Revised IRR of RA 9184 – Two Failed Biddings)

Date: 26 January 2023

Name of Supplier

Quotation No.: 267b - 2022

Address

Please quote your best offer on the item/s listed below, subject to the General Conditions on this page, stating the shortest time of delivery and submit your sealed duly signed quotation not later than 2:00 P.M. of 02 February 2023, at the Bids and Awards Committee Office Conference Room, 3rd Floor Administrative Building, City Hall, Cagayan de Oro City.

NOTE:

1. DELIVERY PERIOD IS THIRTY (30) CALENDAR DAYS FROM THE RECEIPT OF THE NOTICE TO PROCEED.
2. THE FOLLOWING SHALL BE ATTACHED UPON SUBMISSION OF THE QUOTATION:

   A. PhilGEPS Certificate of Registration and membership (Platinum)
   B. Production/Delivery Schedule

Item No.	Quantity	Unit of Issue	Item Description	Unit Price	Total Price
1	4	unit	Dynamic Mic / Basic transducer impedance Typically around 30O - transformers are used within the microphone to transform to desired impedance. Typical frequency response 40 – 15 000 Hz – often		
2	1	unit	Condenser Mic / echnology. 33 mm fixed-charge. Frequency Response. 40 Hz - 20 kHz. Polar Pattern. Cardioid. Output Impedance. 150 ohms. Sensitivity. 23 mV / Pa @ 1 kHz. Signal to Noise Ratio. 84 dB. Maximum SPL. 140 dB. Dynamic Range. 130 dB.		
3	1	unit	Interface Dual Port / Form Factor. Plug-in card ; Interface (Bus) Type. PCI Express ; Networking. Ports. Gigabit Ethernet x 2. Connectivity Technology. Wired. Cabling Type. Ports: Gigabit Ethernet x 2 Networking: Ports Gigabit Ethernet x 2Connectiion Interface (Bus) Type: PCI Express		

			Device Type: Network adapter		
4	2	unit	Mixer / I/O Inputs TOTAL 10ch : Mono (MIC/LINE):4, Stereo(LINE):3 Power CH1, 2 : +30 V Outputs SPEAKERS [L, R], MONITOR OUT [L,R], SUBWOOFER OUT Control and others FOOT SW : Effect Mute on/off Bus Stereo: 1, Effect: 1 Input Channel Function PAD 26 dB (CH1-4) Hi-Z Supported (CH4) EQ HIGH 8kHz +15dB / -15dB EQ MID 2.5kHz +15dB / -15dB EQ LOW 100Hz +15dB / -15dB On-board processors DSP SPX Algorithm Reverb 4 programs, MASTER EQ (SPEECH to MUSIC), Feedback suppressor On-board amplifiers Maximum output power @4ohms 1kHz THD+N less than 10% (CEA2006) : 250 W + 250 W, 1kHz THD+N less than 1% : 110 W + 110 W Maximum output power @8ohms 1kHz THD+N less than 10% (CEA2006) : 170 W + 170 W, 1kHz THD+N less than 1% : 110 W + 110 W Level Meter 6points (-20, -6, 0 , +3, +6, LIMITER)		
5	10	pair	XLR - Male & Female		
6	6	pc	Speak - On		
7	1	roll	Mic Wire / (Stereo Type) 1000 meters		
8	100	m.	Royal Cord #16 / OEM. 312810273_PH-631386504. Royal Cord 16/2 SJT SIZE: 1.25 mm² x 2C, 60° 300V. Cable Type. Cables. Input Voltage (V) 100-240 V.		
9	8	pc	Baby Plug		
10	8	pc	Driver unit / Compression Driver Unit • 200 watts • Impedance 8 ohms • Voice Coil 34.44 mm • Magnet 90x15mm • Sensitivity 102db/wm		
11	4	pc	HDMI cable (3 meters) / 3 mtrs, HDMI to HDMI Cable, Output camera feed to Video Capture Card		
12	2	unit	Equalizer 32 Band / Input Connectors 1/4" TRS, female XLR (pin 2 hot) Power Connector IEC receptacle Unit Weight 6.2 lbs.(2.81 kg) Shipping Weight 7.9 lbs.(3.58kg) Dimensions 3.5" (8.9cm) H x 6"(15.24cm) D x 19" (48.26cm) W		

13	10	pc	PL Plug / Coupling shell thread: 5/8 inch 24 tpi UNEF st...Cable Type: Coaxial Centre pin diameter: Approx 0.156 inches or 4... Diameter: 18.0 mm / 0.71 in (typical)		
14	1	unit	Splitter, 2 PDRTS HDMI / Video Input Interfaces 1 x HDMI Type A Female (Black) Max. Pixel Clock 340 MHz Compliance HDMI (3D, Deep Color, 4K); HDCP Compatible Max. Resolution Up to 4096 x 2160 / 3840 x 2160 @ 60Hz (4:2:0); 4096 x 2160 / 3840 x 2160 @ 30Hz (4:4:4)		
15	1	unit	Compressor/Limiter / Input Connectors 1/4" TRS, female XLR (pin 2 hot) Input Impedance >50kO balanced, >25kO unbalanced Max Input >+24dBu, Balanced or Unbalanced Input Type Electronically balanced/unbalanced, RF filtered Operating Voltage 100 VAC 50/60Hz; 120VAC 60Hz; 230 VAC 50/60 Hz		
16	2	unit	Powered Speaker 15" / Acoustical specifications. 40Hz-18kHz. 1 x 1.7" HF. 1 x 15" LF.Input signal: Balanced 20kO, Unbalanced 10kO ... 300W(RMS); 600W(MUSIC); 1200W(PEAK); 8O ... Cabinet/Case Material: Polypropylene injection moulding. 485 x 460 x 700mm / (19.1 x 18.1 x 27.6in) 545 x 515 x 800mm / (21.5 x 20.3 x 31.5in) 30.5 kg / 67.2 lb.		
17	1	unit	Powered Amps / Specifications ; Impedance, 8O, 4O ; Power Output (per channel) (Continuous, 20 Hz - 20 kHz, <1% THD), 400 W · 600 W ... Weight (unpacked): 60 lb (27.3 kg) Width: 17” (43.2 cm) Height: 6-3/4” (17.2 cm)		
18	2	unit	Passive Sub Woofer / Frequency Range (-10 dB): 32 Hz to 230 Hz Power capacity: 1: continuous/peak Frequency Response (-6 dB): 37 Hz to 230 Hz Configuration: 1 × 18-inch, subwoofer		
19	6	unit	LED PAR RGB / Lamp power:54 x 3W RGB 3 in 1 LED ; Power supply:AC 100-240 V, 50-60 Hz ; Beam angle:25 Deg (15,45 Deg Optional) ; Control:DMX 512 /		
20	1	unit	SCEENE Sitter		

21	1	unit	Rack		
22	10	unit	69" Smart Ultra HD TV / HDMI and Other Connection Ports. Image Credit: Sam-Cat/Creative Commons Screen Resolution. Image Credit: Bretwa/Wikimedia Commons OLED, LCD, and LED Screens Refresh Rate HDR Compatibility Screen Size. Ability to Switch Between Smart and 'Dumb' Mode.		
23	1	pc	Speaker Stand		
24	2	pc	Microphone Stand		
25	1	pc	Snake Cable / 75 ohm coaxial cable High Definition Video cable terminated in RED and WHITE Rear Twist BNCs. The standard 250 foot length Digi design PN 9900-12240-00 part is a two conductor version using Belden 1855A cable internally and a special stiffening/strengthening filler cable		
26	1	pc	Tripod Stand For Lights		
27	1	unit	Camera / EOS Rebel T8i EF-S 18 -55 IS STM lens kit, (850D) Digital SLR. Digital AF/AE single-lens reflex kit lens -24.1-megapixel APS-C CMOS sensor + video Recording -All cross-type 45-point AF (viewfinder) and Dual Pixel CMOS AF (Live View)		
28	1	unit	Camera Lens / Lens #1 EF 17-50mm 1/2		
29	1	unit	Tripod / Professional Tripod Aluminum Alloy Camera Tripod with Fluid Hydraulic Head, Video camera tripod with Fluid Head		
30	1	unit	Wireless Lavalier Mic / Wireless GO Compact Wireless Microphone System, Compact wireless lavalier Clip-on mic system with two mics and one receiver		
31	1	unit	External Camera videomic / NTG4+Shotgun Microphone with Digital Switches and Built-In Rechargeable Battery, External Shotgun Microphone System for Digital Camera with windscreen (Deadcat)		
32	2	unit	Video Studio Continuous Lights / SL-60W photo Lamp with Bowens mount LED Video Shoot Light, Studio Video Light		
33	2	unit	Video Light Diffuser SoftBox / 120cm Octagon Softbox Bowens Mount Ring with Grid Honeycomb, Studio Video Light Softbox Diffuser		

34	2	unit	Video Studio Lights Stand / Heavy Duty Air Cushioned Light Stand for Photography Flash Video Light, Studio Video Light Stand		
35	1	unit	Drone / MAVIC MINI 2 Fly More combo, Photo and video Camera Drone set		
36	1	pc	Studio Backdrop Holder / Photo Studio Backdrop Roller Wall Mount Mounting Manual Control Background Support Elevator with 2 Trifold hooks, 6 Expansion Sticks, 3 Chains and 3 Counter Balance, Studio backdrop for multiple background color needs		
37	3	pc	Seamless Background Paper / 9ft x 36ft Color: Super White, Tech Green, Thunder Grey		
38	1	pc	Video Capture Card / 4k USB 3.0 HDMI Video Card Capture 4k60fps HDR10, 1080P Audio Video Capture Card HDMI to USB 3.0 Acquisition Card		
39	2	pc	Mini HDMI to HDMI Cable / 3 mtrs, Mini HDMI to HDMI Cable, Output camera feed to Video Capture Card		
				Total	

Total Amount in words and figures: _____

Total	

Total Amount in words and figures: _____

By Authority of the BAC:

ATTY. PERCY G. SALAZAR
BAC Chairperson

_____
Printed Name/ Signature

_____
Designation